Reader

## **PXR-51 Mifare Keypad Reader**




 $\bigcirc$ 

## Features

- Conforms to ISO 14443A standard, supporting Mifare® card
- Unique ID or Block read format supported and programmable key value.
- Keypad function. When working with control panel, it provides swiping card, press card number by keypad or swiping card with PIN code to access.
- If the keypad function is disabled but under the entry mode of swiping card with PIN code, the keypad will be enabled automatically after swiping card and then being disabled again immediately after entering PIN code (PXR-51MSK)
- Provides different interfaces to work with access control panel to meet different market requirements
- Provides RS-485 communication interface. It may suit for long distance installation.(PXR-51MSK)
- Wide operation temperature range. It can be installed in different arctic or tropical regions.
- Case sensor detection function.
- Watchdog function secures system free from halting.

## Ordering Information



## Specifications

Model No.	PXR-51MWK	PXR-51MSK
Read Format	Mifare (13.56 MHz)	
Read Range	3-5 cm	
Comm. Interface	Wiegand	RS-485
Keypad	12 Key(0-9, *, #)	
Input Ports	Case Sensor x 1	
ID Setting	No	DIP switch setting
Comm. Baudrate	No	19,200 bps-N-8-1
LED Indicators	Power / Comm.	
Beep Tone	Buzzer	
Power Input	DC 12V / 1A	
Current Consumption	200mA (max)	
Operating Temp.	-20°C~ 70°C / -4°F~ 158°F	
Relative Humidity	20% ~ 80%(Non-condensing)	
Dimentions (LxWxH)(mm)	112 x 77 x 21	