

PXR-62 EM Reader



(SG)



(DG)

Features

- Support 125 KHz-EM card
- Reading distances are around 8~10 cm
- Case sensor detection function
- Watchdog function secures system free from halting
- Provide different communication interface with controller.
- Special model to provides both T2 and Wiegand interfaces, it allow customer to use more flexible. (PXR-62ETW)
- Provide RS-485 communication interface, it may suit for long distance installation.(PXR-62ES)
- Wide operation temperature range, it can be installed in different arctic or tropical regions.

Ordering Information

Package Content: <ul style="list-style-type: none"> • PXR-62 x 1 • Quick Start Guide x 1 • Accessory Pack x 1 • Plate x 1 	
Model No. Identification P X R - 6 2 E S 	Color

Specifications

Model No.	PXR-62ETW	PXR-62ES
Read Format	EM (125 KHz)	
Read Range	8-10 cm(max)	
Comm. Interface	T2 / Wiegand	RS-485
Input Port	Case Sensor x 1	
ID Setting	NONE	DIP switch setting
Comm. Baudrate	NONE	19,200 bps-N-8-1
LED Indicator	Power / Comm.	
Beep Tone	Buzzer	
Power Input	DC 12V / 1A	
Current Consumption	200mA (max)	
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F	
Relative Humidity	20% ~ 80%(Non-condensing)	
Dimension (LxWxH)(mm)	120 x 76 x 27	
Weight (Device)	143g	